

## INFORMATION

Driver: Vincent JacquelinDate/日時: 2024 / 3 / 10Circuit name/サーキット名: RC Drift Master 2024 ItalyTrack Size:  Large  Medium  SmallSurface/路面:  Asphalt  P-Tiles  Carpet  Others Concrete

### GENERAL

A1. Motor Direction:  CCW  CWA2. Operation Mode:  F/B/R  F/B  F/R

A3. Rev. Delay: \_\_\_\_\_ (1.0 ~ 5.0s)

A4. BEC Voltage:  6.0V  7.4VA5. Cutoff Volt:  Off  Auto.V  3.2V (3.0~11.0V)A6. Thermal Protection:  Off  95deg  105deg  130deg

### THROTTLE

B1. Throttle Response: 0.1ms (0.1~3.0ms)B2. PWM Drive Freq:  1.0  4.0  8.0  16  7.0KHz (1~32KHz)B3. Start Power: 2.0% (2.0~16%)B4. Smooth Start Rate:  Off  \_\_\_\_\_ (1.0~30%)

B5. Smooth Start Range: \_\_\_\_\_ (1.0~70%)

B6. Neutral Range: \_\_\_\_\_ (3.0~12%)

### BRAKE

C1. Start. Brake Power:  Off  10.0% (1.0~50%)C2. Max. Brake Power: 100.0% (10~100%)C3. Brake Response: 0.1ms (0.1~3.0ms)C4. Drag Brake:  Off  \_\_\_\_\_ (1.0~30%)C5. Initial Brake Power: 1.0ms (0.1~3.0ms)C6. PWM Brake Freq.: 1.0KHz (0.1~16KHz)C7. Auto Brake:  Off  ON

### BOOST

D1. Boost Timing:  Off  20.0deg (1.0~64deg)D2. Activation Mode:  Throttle  RPMD3. Throttle BST. Control: 55.0% (10~90%)

D4. RPM BST. Control: \_\_\_\_\_ (8~50KR/min)

D5. Initial Boost: \_\_\_\_\_ (1.0~64deg)

D6. Boost Inc. RPM: 1.0deg (1.0~64deg/0.1s)  64deg/InstantD7. Boost Dec. RPM: 1.0deg (1.0~64deg/0.1s)  64deg/Instant

### TURBO

E1. Turbo Timing:  Off  24.0deg (1.0~64deg)E2. Turbo + Slope Inc: 64.0deg (1.0~64deg/0.1s)  64deg/InstantE3. Turbo - Slope Dec: 64.0deg (1.0~64deg/0.1s)  64deg/InstantE4. Turbo Delay:  0% Instant/s  \_\_\_\_\_ (0.1~2.0sec/min)E5. Delay Engage:  Off  ON

### Note

Stock Capacitor

Trace Capacitor

## DATA

Chassis/シャーシ: RDXMotor: ABSOLUTE1 13.5TTiming Advance/進角: 33Spur Gear: 86T Pinion Gear: 18TTire: DS LF4 Comp3