

INFORMATION

Driver : _____ Date/ 日時 : ____ / ____ / ____ Circuit name/ サーキット名 : _____

Track Size : Large Medium Small Surface/ 路面 : Asphalt P-Tiles Carpet Others _____

GENERAL

- A1. Motor Direction : CCW CW
- A2. Operation Mode : F/B/R F/B F/R
- A3. Rev. Delay : _____ (1.0 ~ 5.0s)
- A4. BEC Voltage : 6.0V 7.4V
- A5. Cutoff Volt : Off Auto.V _____ (3.0~11.0V)
- A6. Thermal Protection : Off 95deg 105deg 130deg

THROTTLE

- B1. Throttle Response : _____ (0.1~3.0ms)
- B2. PWM Drive Freq : 1.0 4.0 8.0 16 _____ (1~32KHz)
- B3. Start Power : _____ (2.0~16%)
- B4. Smooth Start Rate : Off _____ (1.0~30%)
- B5. Smooth Start Range : _____ (1.0~70%)
- B6. Neutral Range : _____ (3.0~12%)

BRAKE

- C1. Start. Brake Power : Off _____ (1.0~50%)
- C2. Max. Brake Power : _____ (10~100%)
- C3. Brake Response : _____ (0.1~3.0ms)
- C4. Drag Brake : Off _____ (1.0~30%)
- C5. Initial Brake Power : _____ (0.1~3.0ms)
- C6. PWM Brake Freq. : _____ (0.1~16KHz)
- C7. Auto Brake : Off ON

BOOST

- D1. Boost Timing : Off _____ (1.0~64deg)
- D2. Activation Mode : Throttle RPM
- D3. Throttle BST. Control : _____ (10~90%)
- D4. RPM BST. Control : _____ (8~50KR/min)
- D5. Initial Boost : _____ (1.0~64deg)
- D6. Boost Inc. RPM : _____ (1.0~64deg/0.1s) 64deg/Instant
- D7. Boost Dec. RPM : _____ (1.0~64deg/0.1s) 64deg/Instant

TURBO

- E1. Turbo Timing : Off _____ (1.0~64deg)
- E2. Turbo + Slope Inc : _____ (1.0~64deg/0.1s) 64deg/Instant
- E3. Turbo - Slope Dec : _____ (1.0~64deg/0.1s) 64deg/Instant
- E4. Turbo Delay : 0% Instant/s _____ (0.1~2.0sec/min)
- E5. Delay Engage : Off ON

Note

DATA

Chassis/ シャーシ : _____ Motor : _____ Timing Advance/ 進角 : _____

Spur Gear : _____ Pinion Gear : _____ Tire : _____