

INFORMATION

Driver : _____ Date/ 日時 : ____ / ____ / ____ Circuit name/ サーキット名 : _____

Track Size : ☐ Large ☐ Medium ☐ Small Surface/ 路面 : ☐ Asphalt ☐ P-Tiles ☐ Carpet ☐ Others _____

GENERAL

- A1. Motor Direction : ☐ CCW ☐ CW
- A2. Operation Mode : ☐ F/B/R ☐ F/B ☐ F/R
- A3. Rev. Delay : ☐ 1.0s ☐ 2.0s ☐ 3.0s
- A4. BEC Voltage : ☐ 6.0V ☐ 7.4V
- A5. Cutoff Volt : ☐ Off ☐ 6.5V ☐ 7.0V

THROTTLE

- B1. Throttle Response : ☐ Mild ☐ Middle ☐ Quick
- B2. PWM Drive Freq : ☐ Mild ☐ Middle ☐ Aggress
- B3. Start Power : _____ (3.0 ~ 10.0%)
- B4. Smooth Start Rate : _____ (0.0 ~ 20.0%)
- B5. Smooth Start Range : _____ (0.0 ~ 20.0%)
- B6. Neutral Range : ☐ 3.0s ☐ 4.0s ☐ 5.0s

BRAKE

- C1. Drag Brake : _____ (0.0 ~ 30.0%)
- C2. PWM Brake Freq. : _____ (1.0 ~ 4.0KHz)

BOOST

- D1. Boost Timing : _____ (0.0 ~ 25.0deg)
- D2. Throttle BST. Control : _____ (10.0 ~ 90.0%)
- D3. Initial Boost : _____ (1.0 ~ 10.0deg)
- D4. Boost Inc. RPM : _____ (1.0 ~ 10.0deg/0.1s)

TURBO

- E1. Turbo Timing : _____ (0.0~55.0deg)

Note

DATA

Chassis/ シャーシ : _____ Motor : _____ Timing Advance/ 進角 : _____

Spur Gear : _____ Pinion Gear : _____ Tire : _____