

INFORMATION

Driver : MOCCHIYDate/日時 : 2026 / 3 / 19Circuit name/サーキット名 : G circuitTrack Size : Large Medium SmallSurface/路面 : Asphalt P-Tiles Carpet Others _____

GENERAL

A1. Motor Direction : CCW CWA2. Operation Mode : F/B/R F/B F/RA3. Rev. Delay : 1.0s 2.0s 3.0sA4. BEC Voltage : 6.0V 7.4VA5. Cutoff Volt : Off 6.5V 7.0V

THROTTLE

B1. Throttle Response : Mild Middle QuickB2. PWM Drive Freq : Mild Middle AggressB3. Start Power : 7.0% (3.0 ~ 10.0%)B4. Smooth Start Rate : 0.0% (0.0 ~ 20.0%)B5. Smooth Start Range : 20.0% (0.0 ~ 20.0%)B6. Neutral Range : 3.0s 4.0s 5.0s

BRAKE

C1. Drag Brake : 18.0% (0.0 ~ 30.0%)C2. PWM Brake Freq. : 2.0KHz (1.0 ~ 4.0KHz)

BOOST

D1. Boost Timing : 10.0deg (0.0 ~ 25.0deg)D2. Throttle BST. Control : 30.0% (10.0 ~ 90.0%)D3. Initial Boost : 1.0deg (1.0 ~ 10.0deg)D4. Boost Inc. RPM : 1.0deg/0.1s (1.0 ~ 10.0deg/0.1s)

TURBO

E1. Turbo Timing : 55.0deg (0.0~55.0deg)

Note

2025-7-28 のアップデートデータを使用。

Uses update data for Version
2025-7-28

DATA

Chassis/シャーシ : RDXMotor : ARISE 13.5T

Timing Advance/進角 : _____

Spur Gear : 80TPinion Gear : 23TTire : Rêve D / Topline