

INFORMATION

Driver : _____ Date/ 日時 : ____ / ____ / ____ Circuit name/ サーキット名 : _____

Track Size : ☐ Large ☐ Medium ☐ Small Surface/ 路面 : ☐ Asphalt ☐ P-Tiles ☐ Carpet ☐ Others _____

GENERAL

- A1. Motor Direction : ☐ CCW ☐ CW
- A2. Operation Mode : ☐ F/B/R ☐ F/B ☐ F/R
- A3. Rev. Delay : _____ (1.0 ~ 5.0s)
- A4. BEC Voltage : ☐ 6.0V ☐ 7.4V
- A5. Cutoff Volt : ☐ Off ☐ Auto.V ☐ _____ (3.0~11.0V)
- A6. Thermal Protection : ☐ Off ☐ 95deg ☐ 105deg ☐ 130deg

THROTTLE

- B1. Throttle Response : _____ (0.1~3.0ms)
- B2. PWM Drive Freq : ☐ 1.0 ☐ 4.0 ☐ 8.0 ☐ 16 ☐ _____ (1~32KHz)
- B3. Start Power : _____ (2.0~16%)
- B4. Smooth Start Rate : ☐ Off ☐ _____ (1.0~30%)
- B5. Smooth Start Range : _____ (1.0~70%)
- B6. Neutral Range : _____ (3.0~12%)

BRAKE

- C1. Start. Brake Power : ☐ Off ☐ _____ (1.0~50%)
- C2. Max. Brake Power : _____ (10~100%)
- C3. Brake Response : _____ (0.1~3.0ms)
- C4. Drag Brake : ☐ Off ☐ _____ (1.0~30%)
- C5. Adv Drag Brake Rete : _____ (OFF~100%)
- C6. Adv Drag Brake Range : _____ (00.0~100.0KR/min)
- C7. Initial Brake Power : _____ (0.1~3.0ms)
- C8. PWM Brake Freq. : _____ (0.1~16KHz)
- C9. Auto Brake : ☐ Off ☐ ON

BOOST

- D1. Boost Timing : ☐ Off ☐ _____ (1.0~64deg)
- D2. Activation Mode : ☐ Throttle ☐ RPM
- D3. Throttle BST. Control : _____ (10~90%)
- D4. RPM BST. Control : _____ (8~50KR/min)
- D5. Initial Boost : _____ (1.0~64deg)
- D6. Boost Inc. RPM : _____ (1.0~64deg/0.1s) ☐ 64deg/Instant
- D7. Boost Dec. RPM : _____ (1.0~64deg/0.1s) ☐ 64deg/Instant

TURBO

- E1. Turbo Timing : ☐ Off ☐ _____ (1.0~64deg)
- E2. Turbo + Slope Inc : _____ (1.0~64deg/0.1s) ☐ 64deg/Instant
- E3. Turbo - Slope Dec : _____ (1.0~64deg/0.1s) ☐ 64deg/Instant
- E4. Turbo Delay : ☐ 0% Instant/s ☐ _____ (0.1~2.0sec/min)
- E5. Delay Engage : ☐ Off ☐ ON

Note

DATA

Chassis/ シャーシ : _____ Motor : _____ Timing Advance/ 進角 : _____

Spur Gear : _____ Pinion Gear : _____ Tire : _____