

RS-ST PRO Programmable Setup Sheet



INFORMATION

Driver : _____ Date/ 日時 : _____ / _____ / _____ Circuit name/ サーキット名 : _____

Track Size : ☐ Large ☐ Medium ☐ Small Surface/ 路面 : ☐ Asphalt ☐ P-Tiles ☐ Carpet ☐ Others _____

Chassis/ シャーシ : _____ Motor : _____ Timing Advance/ 進角 : _____

Gyro : _____ Curve : _____ Gain : _____ Servo Horn : _____ Pinion Gear : _____ Spur Gear : _____ Tire : _____

SETUP DATA

TRANSMITTER : ☐ Basic mode ☐ Futaba mode ☐ Sanwa mode

SERVO TRIM : ☐ Left ☐ Right _____ (-20 ~ 0 ~ 20)

TORQUE : _____ (1~35) DAMPER : _____ (1~600) MAX POWER : _____ (1~120)

INTL TORQUE: _____ (1~60) DAMPER POINT : _____ (1~200) FREQUENCY : _____ (1~7)

MID-TORQUE: _____ (1~60) SPEED CURVE : _____ (1~200) DEAD BAND : _____ (1~20)

MAX-TORQUE: _____ (1~60) COUNTER ASSIST : _____ (1~50) DIRECTION : ☐ CW ☐ CCW

TORQUE CURVE: _____ (1~250)

Note

CLS MOTOR
RS-ST PRO